

Octopus



“T” Series

Full-automatic Rotary Ring Stretch Wrapper for High Capacity

- **High Speed Operation
Increases Throughput**

Wraps up to 150 pallets per hour depending on load size and wrap pattern by having two film carriages to apply film simultaneously and independently at the same time

- **Robust Construction
Minimizes Maintenance**

Heavy duty steel frame structure along with a well-balanced ring and belted lifting device results in quiet, efficient performance and minimal maintenance

- **High speed machine
for most demanding
use and high capacity**

Due to increased speed, it is possible to use floor space more efficiently for single line use



- **Simple Installation
Saves Time, Money
and Space**

Requires minimal assembly and less floor space compared to most other styles of wrappers

- **Extremely Versatile
Modular Design
to Meet Changing
Demands**

Accommodates a wide range of pallet load sizes and is offered with comprehensive amount of innovative options

- **Consistency and
Unmatched Flexibility**

Advanced **Easy S** film carriage ensures a higher, more consistent pre-stretch while the ring design allows for unlimited wrap patterns and optimised film usage

- **High capacity and
reliability**

Significant time and labour cost savings by Automatic Reel Change System (RCS) resulting in higher capacity and reliable operation

HALOILA

Machines & Service

www.haloila.com

Octopus “T” series enables to achieve a production speed up to 150 pallets per hour.

Octopus

The Octopus T models: 1850T, 2340T, 2830T

Octopus features

- High wrapping speed offering high capacity
- Unique, positive film tail heat sealing method
- **Easy S** film carriage design offers unmatched performance

The **OCTOPUS “T”** is developed for high-speed production lines within industries such as food & beverage, construction and tissue. It is equipped with a double film carriage and a seaming unit solution. Both film carriages apply film simultaneously and independently resulting in excellent load containment. Top sheet device (to reach dust or splash proof wrapping result) is available as an option. With an optional Fast Cycle conveyor solution it is possible to reduce traditional conveying time to half. Due to increased speed, it is possible to use floor space more efficiently for single line use.

The **OCTOPUS “T”** can be equipped with different automatic reel change systems. RCS II (Reel Change System) is ready to replace automatically either of two reels in the “T” machine. RCS increases flexibility and productivity as a new film cassette will be introduced automatically without operator intervention, when the system senses lack of film or a film break. Another great advantage is that an operator can load a new film reel on to the RCS cassette while the Octopus is wrapping. As the automatic film reel change takes only 40 seconds, it is hard to beat Octopus “T” + RCS package with any other system when time matters. Octopus “T” + RCS will dramatically increase your production rates.


It can accommodate a wide range of pallet load sizes and produces a heat seal finish (with no tail) of the highest quality. The Octopus is silent in operation and easily maintained. This versatile machine is modular in design, allowing for numerous innovative options to help solve your specific stretch packaging challenges.

Options

- **Load stabilizer** ensures unstable loads to remain intact throughout the wrapping operation.
- **Octopus lay on force control** maximizes production efficiency.
- **Integrated top sheet dispenser** provides automatic weather proofing without taking up floor space.
- **Optional top sheet reel lift** descends to floor level for easy loading.
- **For time and labour savings the Automatic Reel Change System (RCS)** which automatically changes the reels of stretch film without manual intervention.
- With the recommended Roping device, the Octopus “T” can create total product to pallet retention (Note: pallet lift required). This roping effect minimizes transport damage and returns.
- **Corner Post Device (CPD)** cost saving system that automatically inserts 4 solid corner posts at the pallet corners.
- **OctoMAX™** performance monitoring system reduces film costs, eliminates downtime and simplifies maintenance.
- **And many more . . .**



1. Film loading takes place outside of the safety fences without interfering the production. Therefore the operator can load a new film reel on to the RCS cassette even while the Octopus is wrapping.



2. Double top sheet dispenser can also be used as an automatic top sheet reel changer when both top sheet film reels are identical in width. In this case, the machine starts to use another reel automatically after the current film reel is finished.

easyS
FILM CARRIAGE

HALOILA

Machines & Service

SIGNODE INDUSTRIAL GROUP

octopus.gb@team.haloila.com | octopus.global@team.haloila.com
www.haloila.com